



# ACCESSORIES

## SKD-2 FLOW CONTROLLER



**TRACER PUMPS**  
LEADING IN MOTION

2023 V1



# FLOW CONTROL SWITCH

## SKD-2



### Operation and Application

The SKD-2 flow control switch starts the pump automatically when pressure decreases (for example taps are opened) and stops it when there is no flow/water shortage (for example taps are closed). It can be used for drinking water or non-potable water piping systems.

### Operating limits

Flow from 0 to 6m<sup>3</sup>/h.

Pipe Water Temperature:

0 - 60°C (but not frozen)

Ambient Temperature:

0 - 45°C

### Technical features

Rated Voltage:	220VAC, 50Hz
Maximum current:	10 A
Protection grade:	IP65
Starting pressure:	1.5 bar
Maximum pressure:	10 bar
Inlet/outlet size:	(1" x 1") BSP

<p><b>REPLACEABLE PC BOARD</b></p>	<p><b>ADJUSTABLE PRESSURE</b></p> <p>cut in pressure adjustable between 1.2 &amp; 1.5 bar</p>
------------------------------------	---

MODEL	INPUT VOLTAGE	FREQUENCY	CURRENT	POWER	
	(V)	(Hz)	(A)	(W)	(HP)
SKD-2	220	50	10	1500	2

### Sectional drawing

